



IQ:330

DUAL ALL-IN-ONE COMPACT ZOOM CAMERA



INTELLIGENCE TO CAPTURE 3 LANES

Incorporating dual 1080p HD images, motorised zoom, high speed ANPR recognition and maxIRange™ pulsed IR lighting in one small but highly efficient unit, the IQ:330 camera offers vehicle-based or compact fixed-site options for users of all-in-one intelligent ANPR cameras.

The Q:330 provides recognition for up to 12m lane width for detection of plates and is simple to set up with truEZoom™ for perfect field of view at distances from 3m up to 20m. Setup is performed using the camera's API or from any browser using the IQ's web setup with live video feed.

The high definition global shutter ANPR camera module is synchronized to upgraded infrared (IR) pulsed LEDs to offer superior license plate recognition to match the increased capture width that 1080p resolution offers.

The IQ:330 performs its ANPR recognition within the camera using a custom embedded processor. Real time recognition is performed on raw 1080p HD images.

The IQ:330 offers store and forward buffering to provide up to one million cached reads or immediate data transfer via an API supporting JSON, FTP, UTM1.2 and Web Services.

The IQ:330 is hermetically sealed to IP68 and can be powered using PoE+ or 9-36V DC to give a single cable install suitable for vehicles or fixed sites where the smaller physical size is appealing.

3 lane (12m) coverage

All-in-One Intelligent Camera

Full HD image with truEZoom™

Dual ANPR with Overview

maxIRange™ Illumination

REASONS TO BUY IQ:330

MULTI LANE – high resolution 1080p images providing excellent recognition

INTEGRATED ANPR ENGINE – to provide high accuracy reads with meta data

JSON WEB SERVICES – simple integration into applications using open interface

ZOOM CAMERAS – fully controllable truEZoom™ for the perfect field of view

POWERFUL PULSED IR – maxIRange™ for true day/night number plate recognition

ECO POWER / PoE+ - low power consumption, optionally powered from 802.3at PoE+

VEHICLE READY – wide range power input allows direct power from vehicle battery

API CONTROL - full control and live feedback of ANPR, camera and IR settings



IQ:330 SPECIFICATION

The IQ:330 is available in two models for short range 4-12mm zoom, or mid-range 8-22mm zoom.

Camera Specifications	IQ:330
Recognition Range	Capture of up to 12m of traffic lanes from 3m to 20m based on 850nm IR on EU retro-reflective plates
Sensor	ANPR: 1/3" 1920(H) x 1080(V) 16:9 global shutter, 25 fps Overview: 1/3" 1920(H) x 1080(V) 16:9 rolling shutter (global optional), 25 fps
Motorised Lens	ANPR: motorized zoom (4-12mm or 8-22mm), focus and p-iris control Overview: motorized zoom (4-12mm or 8-22mm), focus and auto DC iris (p-iris optional)
IR illumination	12 pulsed LED arrays with lenses (850nm standard. White light, 740nm or 940nm optional)
Optical Filters	IR: Bandpass matched to LEDs OV: Day/Night IR Cut Filter (auto/manual)
Camera Control	Integrated web server provides full camera and illuminator setup pages and live preview from any connected browser (no plug-ins required)
ANPR Engine Functionality	
ANPR Processor	Dual Core DSP with co-processor and two channel internal parallel video input
ANPR Software / Presets	ANPR license and configuration upload via web based configuration pages for simple remote management
ANPR Engine Protocol	JSON web services provide full access to overview and plate patch images and metadata as push or pull messages for easy integration into applications (O/S independent) and via web pages
ANPR Metadata	Multiple plate tracking with IDs, full availability of plate movement/size data through field of view
ANPR Storage	Onboard storage 8GB (optionally 32GB) for up to 1 million buffered reads
ANPR Features	Image cropping options for Overview image, advanced de-skew and yaw correction, character spacing validation, country of origin matching, lane determination, direction of travel, plate tracking and geometry
Physical Specifications	
Operating Voltage	PoE+ (803.2at type 2) or 9-36VDC suitable for vehicle battery power
Network Connections	10/100 Base-T physical
Power Consumption	Nominally 12W
Dimensions	138 x 57 x 148 mm (W x H x D) - excluding brackets/sunshield/cable
Weight	1.5kg (3.3lb) excluding mount and sunshield
Enclosure	IP68 hermetically sealed. Hard anodized aluminium with mount options
Temperature / Humidity	-30°C to 55°C operating with relative humidity 0%RH to 100%RH (hermetically sealed)
Service	
Customer Service	Friendly, helpful service for product ordering and repair returns
Technical Support	Comprehensive pre and post-sale technical support for full life of the product
Warranty	12 month warranty, extended warranties and factory repair/replacement programmes available
Long Term Supply	Complete support for the life of the product
Training	Comprehensive product training programmes for customers



MAV Systems Limited,
Lullingstone Park Farm Offices
Eynsford, Kent, UK, DA4 0JA
+44 333 800 3050
www.mav-systems.com
www.anprcameras.com